

Fuga-Pave Porcelain Primer – Part B

Front of Bag

Bullit Point

- Part of the Guaranteed Fuga-Pave A B C External Fixing System
- High strength bonding agent – Enables fixing of porcelain using Fuga-Pave Mortar
- Fibre reinforced
- Suitable for use with all types of paving slabs
- Mix with water

20kg bag

Back of Bag

Description

Fuga-Pave Primer is a cement-based primer which contains fibre reinforcement and specially designed polymer additives to promote bond strength and enable fixing of porcelain and other low absorption types of paving to both hardcore and solid bases. Simply mix the primer powder with water and apply to the back of the paving before fixing in a bed of **Fuga-Pave Mortar**.

It can be used in internal and external domestic and heavily trafficked installations.

Preparation

It is essential that the underside of the paving is clean and dry before the primer is applied. Thoroughly dry brush to remove all dust, dirt or any other material which may impair adhesion. Suitable for use in temperatures between 3°C and 25°C.

Mixing

Add approximately 6.2 litres of cold water to a suitable mixing bucket and gradually introduce the 20kg of powder (approximately 0.3 litres of water/ 1kg of powder used), stirring to blend the mixed primer to a smooth lump-free slurry. It is essential to only mix enough material that can be used within the pot life of the product. The primer has a pot life of around 60 minutes at 20°C, which will be extended in cold conditions and reduced in warm temperatures.

Application

Using a suitable brush or roller, apply the mixed primer slurry over the whole of the underside of each slab at a thickness of 1mm-2mm immediately before laying onto the mortar bed.

Please note that **Fuga-Pave Primer** is a cement-based product and therefore all tools should be washed with clean water immediately after use. Do not empty waste material into the drainage system.

Coverage Figures

Approximately 0.7kg/m²


A 20kg bag will cover approximately 28m²

Storage

Store in dry internal conditions away from direct sunlight between 5-25°C. The product has a 12 month shelf life from date of manufacture.

Health & Safety

HEALTH & SAFETY


<p>CONTAINS CHROMIUM VI DANGER Causes skin irritation. Harmful if swallowed. Causes serious eye damage. May cause respiratory irritation. Keep out of reach of children. Avoid breathing dust. Wear protective gloves and eye protection. Wash hands thoroughly after handling. IF SKIN IRRITATION OCCURS: Get medical advice/attention. IF SWALLOWED: Call a poison centre or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison centre or doctor/physician. Dispose of contents/container in accordance with local/regional regulations.</p>
<p>Norcros Adhesives, Harewood Street, Tunstall, Stoke-on-Trent, Staffordshire, ST6 5JZ Tel: +44 (0) 1782 524140 Fax: +44 (0) 1782 524141</p>

REFER TO PRODUCT AND SAFETY DATA SHEET FOR FULL DETAILS.

Barcode: **5010921476124**