





REMIX DRY MORTAR

Post Mix Concrete



Remix Dry Mortar – Post Mix Concrete is a Kiln Dried , Pre-Blended factory produced quick set concrete that is manufactured for use in fixing all types of wooden, metal and concrete posts.



Properties / Benefits:

- Factory produced concrete mix; incorporating standardized binders and aggregates.
- Pre Bagged in manageable sized plastic weatherproof bags
- Quick Setting
- Requires no mixing before use.

Usage Guide:

- Dig Hole to required size for post.
- Half fill the hole with water and place post in hole.
- Add Post Mix Concrete uniformly around the post until it is above the level of water. Add additional water if dry powder is showing.
- Adjust the post into position and support for approx. 10 minutes until set occurs.

Do not use when ambient conditions are below +5°C or if ground is frozen.



REMIX DRY MORTAR LTD

C5 Premier Business Centre, Newgate Lane, Fareham, Hampshire. PO14 1TY
Tel: 01329 231200 Fax: 01329 826341
www.remixdrymortar.co.uk



REMIX DRY MORTAR Post Mix Concrete

Post Shape & Size	Hole Size (Width x Depth)	Approximate Number of Bags required
Round 2" (50mm)	6" (150mm) x 12" (300mm)	1/3 Bag
	6" (150mm) x 18" (450mm)	1/2 Bag
	6" (150mm) x 24" (600mm)	3/4 Bag
	8" (200mm) x 12" (300mm)	2/3 Bag
	8" (200mm) x 18" (450mm)	1 Bag
	8" (200mm) x 24" (600mm)	1 1/2 Bags
Square 3" (75mm)	8" (200mm) x 18" (450mm)	3/4 Bag
	8" (200mm) x 24" (600mm)	1 Bag
	8" (200mm) x 30" (750mm)	1 1/3 Bags
	12" (300mm) x 18" (450mm)	2 1/4 Bags
	12" (300mm) x 24" (600mm)	3 Bags
	12" (300mm) x 30" (750mm)	3 3/4 Bags
Square 4" (100mm)	8" (200mm) x 18" (450mm)	2/3 Bag
	8" (200mm) x 24" (600mm)	3/4 Bag
	8" (200mm) x 30" (750mm)	1 Bags
	12" (300mm) x 18" (450mm)	2 Bags
	12" (300mm) x 24" (600mm)	2 3/4 Bags
	12" (300mm) x 30" (750mm)	3 1/2 Bags

It is the customers responsibility to monitor and control water addition on site, therefore Remix Dry Mortar Ltd are unable to guarantee specific strengths for Remix Post Mix Concrete.

REMIX Post Mix Concrete should not be used for structural or reinforced concrete applications and where prevailing exposure conditions require a concrete grade above DC-1.

DELIVERY/STORAGE:

In plastic bags on fork-liftable shrink wrapped pallets.

All bags must be sheltered from the weather and stored in a frost-free, cool and dry location, avoiding direct contact with the ground.

All bags should be kept sealed until use, avoid using pre-opened or damaged bags.

H & S:

CONTAINS CEMENT: Contact with wet or dry concrete or mortar can result in Irritation, Dermatitis and Burns (skin ulceration)

WEAR CORRECT PPE: Prevent skin contact where the possibility of splashing exists by wearing suitable protective clothing and eye protection. Wash the infected area without delay where skin contact occurs either directly or through saturated clothing. If eye contact occurs the area must be immediately and thoroughly irrigated with clean water.

Please refer to the Remix Dry Mortar – Health and Safety Data Sheet for further advice and information.



REMIX DRY MORTAR LTD

C5 Premier Business Centre, Newgate Lane, Fareham, Hampshire. PO14 1TY

Tel: 01329 231200 Fax: 01329 826341

www.remixdrymortar.co.uk